

S C M 7 : 2 - w a y p a s s i v e



Available in cherry and black ash veneer. Limited other finishes by special order.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk

Features

- New ATC designed and built 25mm soft dome HF unit with precision alloy wave guide.
- 125mm ATC mid/bass unit with integral soft dome.
- In-house, hand-wound precision flat wire coil.
- 3Kg optimised motor assembly.
- Massive optimised motor assembly.
- Flat impedance curve allowing easy load for amplifiers.
- 6 year warranty.

Specifications

Drivers : HF 25mm Neodymium, Mid/LF 125mm

Matched Response : +/- 0.5dB

Frequency Response (-6dB) : 60Hz-22kHz

Dispersion : ±80° Coherent Horizontal, ±10° Coherent Vertical

Sensitivity : 84dB @ 1W @ 1metre

Max SPL : 103dB

Recommended Power Amplifier : 75 to 300 Watts

Nominal Impedance : 8 Ohm

Crossover Frequency : 2.5kHz

Connectors : Binding Posts/4mm Plugs, bi-wire

Cabinet Dimensions (HxWxD) : 300x174x215mm

Weight : 7.5kg

ATC reserves the right to vary products and specifications without prior notice.