

## SCM12 PRO: 2-way passive



### Features

- Compact high performance 2-way studio monitor.
- Ideally suited to:
  - critical near-field listening applications in all control rooms
  - LCR surround monitoring in small-to-medium control rooms.
- Proprietary ATC 150mm/6" CLD Mid/Bass Driver.
- Proprietary ATC 25mm/1" Dual Suspension Tweeter.
- 6 year warranty.

### Specifications

- Drivers :** HF ATC 1"/25mm dual suspension Soft Dome (SH25-76 6 Ohm)  
LF ATC 6"/150mm Constrained Layer Damping (CLD) (SB50-150CLD 8 Ohm)
- Amplitude Linearity :** 80Hz - 16kHz (+/-2dB)
- Cut Off Frequencies :** 56Hz - 22kHz (-6dB freestanding)
- Dispersion :** ±80° Coherent Horizontal, ±10° Coherent Vertical
- Maximum Continuous SPL :** 108dB (per pair @ 1m)
- Crossover Frequency :** 2.2kHz
- Recommended Power Amplifier :** 75 to 300 Watts
- Nominal Impedance :** 8 Ohm
- Connectors :** Binding Posts/4mm Plugs, bi-wire
- Cabinet Dimensions (HxWxD) :** 400x238x235mm/15.7"x9.4"x9.3"
- Weight :** 11kg/24lbs (per cabinet)

ATC reserves the right to vary products and specifications without prior notice.



#### Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email [info@atc.gb.net](mailto:info@atc.gb.net) Website [www.atcloudspeakers.co.uk](http://www.atcloudspeakers.co.uk)