

SCM12 PRO: 2-way passive



Features

- Compact high performance 2-way studio monitor.
- Ideally suited to:
 - critical near-field listening applications in all control rooms
 - LCR surround monitoring in small-to-medium control rooms.
- Proprietary ATC 150mm/6" CLD Mid/Bass Driver.
- Proprietary ATC 25mm/1" Dual Suspension Tweeter.
- 6 year warranty.

Specifications

- Drivers :** HF ATC 1"/25mm dual suspension Soft Dome (SH25-76 6 Ohm)
LF ATC 6"/150mm Constrained Layer Damping (CLD) (SB50-150CLD 8 Ohm)
- Amplitude Linearity :** 80Hz - 16kHz (+/-2dB)
- Cut Off Frequencies :** 56Hz - 22kHz (-6dB freestanding)
- Dispersion :** ±80° Coherent Horizontal, ±10° Coherent Vertical
- Maximum Continuous SPL :** 108dB (per pair @ 1m)
- Crossover Frequency :** 2.2kHz
- Recommended Power Amplifier :** 75 to 300 Watts
- Nominal Impedance :** 8 Ohm
- Connectors :** Binding Posts/4mm Plugs, bi-wire
- Cabinet Dimensions (HxWxD) :** 400x238x235mm/15.7"x9.4"x9.3"
- Weight :** 11kg/24lbs (per cabinet)

ATC reserves the right to vary products and specifications without prior notice.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk